

AC/DC[®] Transformers

www.acdc.com.tr



Isolation Transformers 3 Phase Input - 3 Phase Output



100 kVA

- Isolation Class : B,F or H
- Star, Delta, Zig-Zag and required angle of phase
- Laked Under Vacuum
- Dried in oven
- Construction Specification: Open type or protected type
- Plate or Ferrit Nuve
- 2 years warranty
- 10 years space part warranty

TÜV
AUSTRIA
HELLAS
EN ISO 9001:2008

CE, ISO 9001

Your Positive Energy source ...

MODEL	Tr3U-1003
The Feature of Transformer	Isolation Transformer
Type	Dry Type
Brand	AC/DC
Power	100 kVA
Isolation Class	Class B (120 °C), Class F (155 °C) or Class H (180 °C)
Place of Use	Indoor , Outdoor (Optional)
With Box / Without Box	Without Box, With Box (Optional)
Colling	Naturel Air (AN) or Forced Air (AF)
Protection Class	IP20, IP23 (Optional), IP54 (Optional)
Connections Group	YY, DY or another connect groups
Primer Voltage	400 VAC
Primer Frequency	50 / 60 Hz.
Primer Current	150 A
Seconder Voltage	400 VAC
Seconder Frequency	50 / 60 Hz.
Seconder Current	144 A
Endurance Voltage	3 kV RMS (1 Minute)
Connection	As per to customer requirements: All types of terminals and lugs
Colour	RAL 7032 (Can be changed upon request)
Dimensions (W x H x L) (cm)	100 x 110 x 75
Weight (kg)	600 kg.
Warranty	2 Year
TRANSFORMER LIFETIME	10 YEARS

*** AC/DC reserves the right to make any changes to data without prior notice.

Update: 06 / 08 / 2012

